

# COS-50



# PCT

Professional Coating  
Technologies, Inc.

## WE PROTECT YOUR WATER

### **General Description:**

COS-50 is an environmentally friendly, non-tracking membrane for seal coat pavements. Our COS-50 forms a high density matrix coating protecting the pavement. This matrix encapsulates and binds all of the aggregates together, forming a water resistant membrane. Once applied properly the COS-50 will extend the roadway for an additional 2 years and provide the following benefits:

- Lower pothole maintenance
- Water & freeze thaw resistant surface
- Eliminates flying aggregate problems
- Seals surface cracks



### **Directions:**

1. Spray COS-50 from a distributor truck at a rate of .12-.18 gallons per sq yard.
2. Allow 30 min to 2 hrs to completely cure, treated road may be opened for traffic after 30 min if humidity is below 50%
3. COS-50 may be heated and applied at a temperature of 145F-185F for a quicker drying time.
4. For best results do not use in the rain!
5. Complete final blade work to road.
6. Finish treated surface with steel roller wheel.
7. If desired 1 part ABS-65 to 2-5 parts water may be sprayed for a fog seal prime.

Manufactured By:

Professional Coating Technologies Inc  
1001 Mt Lebanon Rd  
Cedar Hill TX.75014  
972.291.7474  
[www.pctworldwide.com](http://www.pctworldwide.com)

*PCT Inc, an environmentally friendly  
company*

*Earth Friendly Products*